



PONDSEAL 20

DESCRIPTION

PONDSEAL 20 is an all natural unaltered high swelling sodium bentonite. PONDSEAL 20's high swelling properties makes it a preferred choice for all your compacted layer water containment membranes.

APPLICATION

- Soil Sealant
- Reservoirs
- Municipal Landfills
- Sanitation Lagoons
- Hazardous Storage
- Tailings Ponds
- Leach Pads
- Canals
- Tanks
- Ponds

TYPICAL PROPERTIES

Product Specification

Color
Density
Swell
Moisture

Typical SURESEAL

Tan/Red
70 lbs ft³ (compact)
22 cc (Average)
8 to 13 wt.%

SIEVE ANALYSIS

This analysis is an average, variations can apply

SCREEN MESH	% PASSING
40	90
80	60
100	50
200	30

ADVANTAGES

- 100 % Natural
- Very Low Permeability
- Versatility
- Cost Efficiency
- Mixes Very Well With Soils
- Excellent Hard Water Performance

MIXING

The percent of PONDSEAL 20 used should be determined thru permeability testing and user specification requirements.

Permeability testing is available at Redmond Minerals upon request.

PAKAGING

PONDSEAL 20 is available in BULK and 3,000 lb. BULK BAGS

AVAILABILITY

To order PONDSEAL 20 please contact us at 1-866-440-2529