

PONDSEAL 20

DESCRIPTION

PONDSEAL 20 is an all natural unaltered high swelling sodium bentonite. PONDSEAL 20's high swelling properties makes it a preferred choice for all your compacted layer water containment membranes.

APPLICATION

- Soil Sealant
- Reservoirs
- Municipal Landfills
- Sanitation Lagoons
- · Hazardous Storage

- Tailings Ponds
- · Leach Pads
- Canals
- Tanks
- Ponds

This analysis is typical, variations can apply

TYPICAL PROPERTIES

Product Specification

Color Density Swell Moisture

Typical PondSeal 20

Tan/Red 70 lbs/ft³ (compact) 20 cc 8 to 13 wt.%

This analysis is typical, variations can apply

SIEVE ANALYSIS

SCREEN MESH	%
+20	1
+50	12
+100	33
+200	45

ADVANTAGES

- 100 % Natural
- · Very Low Permeability
- Versatility

- Cost Efficiency
- Mixes Very Well With Soils
- Excellent Hard Water Performance

MIXING

The percent of PONDSEAL 20 used should be determined thru permeability testing and user specification requirements.

Permeabiliy testing is available at Redmond Minerals upon request.

PAKAGING

PONDSEAL 20 is available in BULK and 3,000 lb. BULK BAGS

AVAILABILITY

To order PONDSEAL 20 please contact us at 1-866-440-2529