



# PONDSEAL 200

## **DESCRIPTION**

PONDSEAL 200 is an all natural unaltered high swelling sodium bentonite. PONDSEAL 200's high swelling properties makes it a preferred choice for all your compacted or pure layer water containment membranes

## **APPLICATION**

- Soil Sealant
- Reservoirs
- Municipal Landfills
- Sanitation Lagoons
- Hazardous Storage
- Tailings Ponds
- Leach Pads
- Canals
- Tanks
- Ponds

## **TYPICAL PROPERTIES**

Product Specification	Typical SURESEAL
Color	Tan/Red
Density	70lbs ft <sup>3</sup> (compact)
PH	8.5 to 9.0
Swell	25 cc
Moisture	7 to 12 wt%

## **SIEVE ANALYSIS**

This analysis is an average, variations can apply

SCREEN MESH	% PASSING
1/2	100
6	91
20	77
200	10

## **ADVANTAGES**

- 100 % Natural
- Very Low Permeability
- Versatility
- Cost Efficiency
- Mixes Very Well With Soils
- Excellent Hard Water Performance

## **MIXING**

The percent of SURESEAL used should be determined thru permeability testing and user specification requirements. Permeability testing is available at Western Clay upon request.

## **PAKAGING**

PONDSEAL 200 is available in BULK and BULK BAGS

## **AVAILABILITY**

To order PONDSEAL 200 please contact us at 1-866-440-2529