

PONDSEAL 200

DESCRIPTION

PONDSEAL 200 is an all natural unaltered high swelling sodium bentonite. PONDSEAL 200's high swelling properties makes it a preferred choice for all your compacted or pure layer water containment memberanes

APPLICATION

- Soil Sealant
- Reservoirs
- Municipal Landfills
- Sanitation Lagoons
- Hazardous Storage

Moisture

- Tailings Ponds
- · Leach Pads

6 to 10 wt%

- Canals
- Tanks
- Ponds

This analysis is typical, variations can apply

TYPICAL PROPERTIES

Product Specification
Color
Density
PH
Swell
Swell
Typical PondSeal 200
Tan/Red
70lbs/ft³ (compact)
8.5 to 9.0
24 cc

This analysis is typical, variations can apply

SIEVE ANALYSIS

SCREEN MESH	%
+20	0
+100	7
+200	27

ADVANTAGES

- 100 % Natural
- Very Low Permeability
- Versatility

- Cost Efficiency
- Mixes Very Well With Soils
- Excellent Hard Water Performance

MIXING

The percent of SURESEAL used should be determined thru permeability testing and user specification requirements.

Permeability testing is available at Western Clay upon request.

PAKAGING

PONDSEAL 200 is available in BULK and BULK BAGS

AVAILABILITY

To order PONSEAL 200 please contact us at 1-866-440-2529